


## THE STEERING OIL TUBE AND WIRE HARNESS ARE ARRANGED INDEPENDENTLY



### PRODUCT FEATURE

- Reliable U-Joint transmission and V-type support
- Largely Improved driver's comfort
- Easier and quicker maintenance
- Thumb control system (optional)
- 10% enlarged driving space
- Cooling ability 10 improved
- Improved stability and mean-time between failures (MTBF) 40% longer



### THE MAIN PARAMETER

Model	unit	CPCD20/CP (Q)(Y)D20	CPCD25/CP (Q)(Y)D25
Power Unit		Diesel	Diesel
Rated Capacity	kg	2000	2500
Load Center	mm	500	600
Max.Lifting height	mm	3000	3000
Max.Fork lifting height	mm	4039	4039
(with backrest)			
Overall length	mm	3450/2530	3675/2605
(with/without forks)			
Overall width	mm	1150	1150
Overall height	mm	2150	2150
(overhead guard)			
Wheel base	mm	1600	1600
Min.Turning radius	mm	2180/160	2250/160
(exterior/interior)			
Mast tilting angle	deg	6/10	6/10
Max.Travelling speed (loaded/unloaded)	Km/h	18/19	18/19
Lifting speed (loaded/unloaded)	mm/s	670/700	660/730
Lowering speed (loaded/unloaded)	mm/s	560/460	420/320
Max.Drawbar speed (loaded/unloaded)	KN	18.3/12.4	19.3/12.8
Max.Gradability	%	34/28	32/24
(loaded/unloaded)			
Total weight	kg	3660	3880

Engine model and main specification for option

Engine model	Rated power/rotating speed (KW/rpm)	Rated torque/rotating speed (Nm/rpm)	Engine displacement (L)	Engine cylinder number-Bore*stroke	Emission
GM 3.0	60/2700	203/1600	3	4-101.6*91.44	CARB4/EPA STAGE II
GCT K21	31.6/2250	143.7/1600	2.066	4-89*83	
GCT K25	37.4/2300	176.36/1600	2.488	4-89*100	
ISUZU 4JG2	36/2450	170/1700	3.069	4-96.4*107	EURO STAGE IIIA
CUMMINS QSF 2.8	36.6/2600	186/1100-1600	2.8	4-94*100	EURO STAGE IIIA