

THE STEERING OIL TUBE AND WIRE HARNESS ARE ARRANGED INDEPENDENTLY



PRODUCT FEATURE

Anti-misoperation electronic parking brake improves safety and operation convenience;

Equipped with a double guide wheel torque converter gearbox, which can realize stepless speed change;

Adopt a rear-mounted suction cooling system and an all-aluminum plate-fin radiator to improve heat dissipation performance and ensure that the engine and gearbox and other parts work in the best temperature range;

Use maintenance-free wet brake bridge to improve braking reliability;

Full set of LED lamps;

4.3-inch LCD color screen smart instrument, comprehensive monitoring of truck status;

Intelligent vehicle networking and fleet management systems can monitor the daily use of forklifts, perform big data analysis, and provide reports and other documents;

The use of tailstock-less counterweights reduces the center of gravity of the truck and improves stability;

The optimized hydraulic system reduces pressure loss, highlights energy saving and high efficiency, and effectively reduces the fuel consumption of the truck;

THE MAIN PARAMETER

Performance parameters		CPCD40	CPCD45	CPCD50
Model				
Drive type			Diesel	
Operator type			Seated	
Rated capacity	Kg	4000	4500	5000
Load center distance	mm		600	
Standard mast lifting height	mm		3000	
Overall Length(without fork)	mm	3120	3165	3230
Overall width	mm		1450	