

# THE STEERING OIL TUBE AND WIRE HARNESS ARE ARRANGED INDEPENDENTLY



## PRODUCT FEATURE

New H series is the key product which HELI blockbuster launches. Based on the high technology, mass manufacturing capability and experienced sales and services of HELI, new H series becomes a milestone of HELI's products which fully consider the needs of market and customers

### Improved performance, superior quality

- Vibration 20% reduced
- Noise 3dB reduced
- Workspace 45% increased
- Operator's view 20% improved
- Working efficiency 20% improved
- Loading capacity increased over 5%
- Stability 5% improved
- Reliability 40% improved
- Engine hood open angle increased to 80°



## THE MAIN PARAMETER

Model	unit	CPC(D)10/CP(Q)(Y)D10	CPC(D)16/ CP(Q)(Y)D16	CPC(D)18/ CP(Q)(Y)D18
Power Unit		Diesel/Gasoline/LPG/Dual Fuel		
Rated Capacity	kg	1000	1600	1760
Lead Center	mm	600		
Standard lift height	mm	3000		
Free lift height	mm	162	165	165
Overall length(with fork/without fork)	mm	3197/2277	3201/2281	3219/2299
Overall width	mm	1070		
Overall height(overhead guard)	mm	2140		
Wheel base	mm	1450		
Total Weight	kg	2458	2760	2890

Engine model and main specification for option

Engine model	Rated power/rotating speed	Rated torque/rotating speed	Engine displacement	Engine cylinder number-Bore*stroke	Emission	Engine type
	(KW/rpm)	(Nm/rpm)	(L)			
ISUZU C240	34.3/2600	137.7/1800	2.369	4-86*102	Euro Stage3A	Diesel
GCT K21	31.5/2200	140/1600	2.066	4-89*83		GAS/LPG
GCT K15	23.6/2400	103/1600	1.486	4-76.6*63		GAS/LPG
KUBOTA V2403	34.1/2400	166.9/1600	2.434	87*102.4	EURO III / EPA T4I	Diesel
QUANCHAI 4B4-45V32	32/2600	132/1800	2.27	4-86*100		Diesel
KUBOTA WG2603	GAS:42.8/2600 LPG:43.5/2600	GAS:163.3/1800 LPG:173.7/1400	2.491	4-88*102.4	EAP/CARB/EU Stage V	GAS/LPG
XINCHANG 4N23G31	30/2600	131/1800	2.27	4-86*100		Diesel