

THE STEERING OIL TUBE AND WIRE HARNESS ARE ARRANGED INDEPENDENTLY



PRODUCT FEATURE

New H series is the key product which HELI blockbuster launches. Based on the high technology, mass manufacturing capability and experienced sales and services of HELI, new H series becomes a milestone of HELI's products which fully consider the needs of market and customers

Improved performance, superior quality

- Vibration 20% reduced
- Noise 3dB reduced
- Workspace 45% increased
- Operator's view 20% improved
- Working efficiency 20% improved
- Loading capacity increased over 5%
- Stability 5% improved
- Reliability 40% improved
- Engine hood open angle increased to 80°

THE MAIN PARAMETER

Model	unit	CPCD20/CP(0)(Y)020	CPCD25/CP(0)(Y)025
Power Unit		Diesel/Gasoline/LPG/Dual Fuel	
Rated Capacity	kg	2000	2500
Load Center	mm	500	500
Max.Lifting height	mm	3000	3000
Max.Fork lifting height (with backrest)	mm	4030	4030
Overall length (with/without forks)	mm	3600/2680	3708/2638
Overall width	mm	1160	1160
Overall height (overhead guard)	mm	2160	2160
Wheel base	mm	1660	1660
Min.turning radius (exterior/interior)	mm	2170/180	2240/180
Mast tilting angle	deg	6°/12°	6°/12°
Total weight	kg	3660	3880

Engine model and main specification for option						
Engine model	Rated power/rotating speed	Rated torque/rotating speed	Engine displacement	Engine cylinder number-Bore*stroke	Emission	Engine type
	(KW/rpm)	(Nm/rpm)	(L)			
ISUZU C240	35.4/2500	139.9/1800	2.369	4-86*102	Euro Stage IIIA	Diesel
GCT K25	37.4/2400	176.5/1600	2.488	4-89*100		Gasoline or LPG
ISUZU 4JG2	34.1/2400	165.9/1600	2.434	4-87*102.4	Euro Tier IIIA	Diesel
Mitsubishi S4S	35.3/2250	177/1700	3.331	4-97*120	EURO STAGE IIIA	Diesel
KUBOTA WC2503	GAS:42.8/2600 LPG:43.5/2600	GAS:163.3/1800 LPG:173.7/1400	2.491	4-88*102.4	EPA/CARB/EU StageV	Gasoline or LPG
CUMMINS QSF 2.8	36/2500	186/1100~1600	2.8	4-94*100	EURO STAGE IIIA	Diesel