

# THE STEERING OIL TUBE AND WIRE HARNESS ARE ARRANGED INDEPENDENTLY



## PRODUCT FEATURE

New H series is the key product which HELI blockbuster launches. Based on the high technology, mass manufacturing capability and experienced sales and services of HELI, new H series becomes a milestone of HELI's products which fully consider the needs of market and customers

Improved performance, superior quality

- Vibration 20% reduced
- Noise 3dB reduced
- Workspace 45% Increased
- Operator's view 20% Improved
- Working efficiency 20% Improved
- Loading capacity Increased over 5%
- Stability 5% Improved
- Reliability 40% Improved
- Engine hood open angle increased to 80°



## THE MAIN PARAMETER

Model	unit	CPD30/CP(Y)D30	CPD36/CP(Y)D36
Power Unit		Diesel/Gasoline/LPG/Dual Fuel	
Rated Capacity	kg	3000	3600
Load Center	mm	600	600
Max.Lifting height	mm	3000	3000
Max.Fork lifting height (with backrest)	mm	4245	4236
Overall length (with/without forks)	mm	3818/2748	3836/2766
Overall width	mm	1225	1225
Overall height (overhead guard)	mm	2170	2170
Wheel base	mm	1700	1700
Min.Turning radius (exterior/interior)	mm	2400/200	2420/200
Mast tilting angle	deg	6/12	6/12
Total weight	kg	4400	5000

Engine model and main specification for option					
Engine model	Rated power/rotating speed	Rated torque/rotating speed	Engine displacement	Engine cylinder number- Bore*stroke	Emission
	(KW/rpm)	(Nm/rpm)	(L)		
ISUZU 4JG2	44.9/2450	184.7/1600~1800	3.06	4-96.4*107	
ISUZU C240	36.4/2600	139.9/1800	2.369	4-86*102	Euro Stage IIIA
GCT K25	37.4/2400	176.6/1600	2.488	4-89*100	
Mitsubishi S4S	36.3/2260	177/1700	3.331	4-94*120	Euro Stage IIIA
KUBOTA WG2603	GAS:42.8/2600 LPG:43.5/2600	GAS:163.3/1800 LPG:173.7/1400	2.491	4-88*102.4	EPA/CARB EU Stage V
CUMMINS QSF 2.8	36.6/2600	186/1100-1600	2.8	4-94*100	EURO STAGE IIIA